


# LVC-5000-B I / B2 Fanless In-Vehicle NVR with 4 GbE PoE ports and CAN Bus Support



## Features

### Multiple PoE LAN ports to support Transport Surveillance

This mobile NVR with 4 PoE ports (IEEE 802.3af) is suitable for IP Video Surveillance and real-time recording applications.

### Designed for MIL-STD-810G with Extreme Vibration Resistance

LVC-5000-B Series is in compliance with MIL-STD-810G vibration and shock standards and includes SSD storage and a Suspension Kit to further improve robustness.

### Fanless Design with Corrugated Aluminum

The corrugated aluminum casing lets heat dissipate through the top of the device, allowing for a fanless design.

### Convenient DC output

The LVC-5000-B Series offers 12VDC output (max 1A) for external devices, operational in concert with the Ignition Power Management feature.

### Vehicle Ignition Power Management

Detects vehicle ignition on/off status and allows flexible control of the delay time via software utility.






## Modularized and customizable design

The LVC-5000-B Series design features the Lanner Proprietary Internal Multi-IO Interface, which carries signals for 2 USB ports, 4 x UART, 4 x Digital I/O, 2 x PCIe, and 1 x SATA 2.0. This allows for customized add-on modules for future features expansion.

## Settings and Installation via the front panel

MCU setting and CF card and SIM card installation is easy to access simply by opening the front panel.

**Dimensions: 273.8 x 72 x 188 mm (10.78" x 2.84" x 7.4" )**



## Digital I/O

The DIO design includes 12V Level GPIO, audio, MCU TX/RX and also includes 2x DI (Digital Input from MCU) which can connect sensors to detect the environment. Once defined events occur, the LVC-5000 series can be turned on automatically.

## CAN Bus Module

LVC-5000-B1/B2 is designed to act as a bridge between Heavy Duty vehicle protocol and UART interface:

- J1939 and J1708 protocols
- Configurable via AT command
- ASCII and HEX CODE Format Output (Optional for LVC-5000-B1)

## Preliminary Specifications

<b>Dimensions (WxHxD)</b>		273.8 x 72 x 188 mm (10.78" x 2.84" x 7.4" )
<b>Processor</b>		LVC-5000-B1: Intel® Celeron® 1047UE LVC-5000-B2: Intel® Core™ i7-3517UE Processors
<b>Chipset</b>		Intel HM65
<b>System Memory</b>	Technology	DDR3 SO-DIMM x1 ( Factory default: 4GB module pre-installed )
	Max. Capacity	Up to 8GB
<b>Storage</b>	SATA/CF	B1: Removable 2.5" SSD/HDD drive bay x1, Internal drive bay x1, CF socket x1 B2: Removable 2.5" SSD/HDD drive bay x1, CF socket x1
	<b>Ethernet Controller</b>	Intel 82583V x5
<b>Graphic Controller</b>		Intel integrated HD graphic engine
<b>Audio Controller</b>		Realtek ALC886 HD codec
<b>IO</b>	LAN	LVC-5000B1/B2: GbE RJ45 x 5
	Display	DVI-D, maximum resolution up to 1920x1200@75Hz VGA, maximum resolution up to 2048x1536@60Hz HDMI, maximum resolution up to 1920x1200@75Hz
		Dual display supports Independent, clone and extended mode.
	Audio	Mic-in and Line-out with 2 watt by terminal block MIO connector
	Serial I/O	1x RS-232/422/485 both with RI/5V/12V
	GPS	Ublox NEO-7N GPS receiver module
	G-sensor	ADXL 345
	Digital I/O	4x DI and 4x DO with 5V/12V Level by jumper setting 2x DI (from MCU) 3.3V Level 2x DO control relay with contact current @ 2A
		USB 2.0
	Power Input	3-pin terminal block (+, -, ignition)
	Power Output	12 VDC/1A
	Expansion	Mini-PCIe x3 (Three with SIM card slot)
	CAN Bus	Support J1939 and J1708 protocols (Optional for LVC-5000-B1) Baud Rate: 9600, 19200, 38400, 57600, 115200
	PoE	PoE x4, IEEE 802.3af, Standard PoE
	Others	External: 5x SMA antenna hole, Remote Power switch Internal: Lanner Proprietary MIO
<b>Power Input</b>		+9~36VDC input range, with ignition delay on/off control
<b>PoE Power Module</b>		Internal integrated
<b>OS Support</b>		Linux: Redhat Enterprise 5/ Fedora 14. Linux Kernel 2.6.18 or later Windows: XP embedded ; Win7 Pro FES/Embedded; Win8
<b>Certifications</b>		CE, FCC Class A, E13, RoHS
<b>Compliance</b>		Vibration: MIL-STD-810G, Method 514.6 Shock: MIL-STD-810G, Method 516.6
<b>Operating Temperature Range</b>	Extended	With Selected Industrial Components: -20~60°C/-4~140°F
	Standard	With Commercial Components: -5~45°C / 23~113°F

## Ordering Information

<b>LVC-5000-B1</b>	Intel® Celeron® 1047UE In-Vehicle NVR Computer, with Intel GbE x4 Ports PoE for IP cameras. 4GB DDR3 Memory included 1x 2.5" Removable Drive Bay, 1x Internal drive bay, Mini-PCle x3 with three SIM card reader, USB x4, COM x2, DIO, Audio, HDMI, DC Power input +9~36Vdc with Ignition, Suspension Kit included.
<b>LVC-5000-B2</b>	Intel® Core i7-3517UE In-Vehicle NVR Computer, with Intel GbE x5 Ports (PoE x4) for IP cameras. 4GB DDR3 Memory included, 2.5" Removable Drive Bay, CAN Bus x 1, Mini-PCle x3 with three SIM card reader, USB x4, COM x2, DIO, Audio, HDMI, DC Power input +9~36Vdc with Ignition, Suspension Kit included.