

CM1203

Expandable Type for IBASE Mini-ITX Motherboards

CM1201

Expandable Type for IBASE Mini-ITX Motherboards (except LGA775-based)



Features

- Mini-ITX system supports IBASE Mini-ITX motherboards
- Available in black color
- Supports 2x PCI slots
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W power supply
- Wall mount kit included

Specifications

System Mainboard	IBASE Mini-ITX motherboards
Chassis Color	Black
Construction	SECC
Front Panel External I/O	N/A
Rear Panel External I/O	Flexible IBASE Mini-ITX motherboard's I/O shields, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors 4x DB9 / DB15 (RS232 / VGA) 1x PCI expansion slot AC-Inlet
Storage	1x 3.5" HDD drive bay
Power Supply	Output Power: DC 180W or 250W (ATX Power) Input Voltage: 90~264VAC full range
Mounting	Optional wall mount kit
Dimensions	345mm(W) x 225mm(D) x 100mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CM1203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP242, IP118-R riser card & I/O LCM)
CM1203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & I/O LCM)

* Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.

Features

- Mini-ITX system supports IBASE Mini-ITX motherboards except LGA775-based
- With motherboard's I/O shields and extra 2x USB ports
- Available in black color
- LEDs for Standby and Power
- One 2.5" HDD drive bay
- Supports one PCI slot
- Optional 60W power supply
- Wall mount kit included

Specifications

System Mainboard	IBASE Mini-ITX motherboards (except LG775-based)
Construction	SECC
Chassis Color	Black
Front Panel External I/O	N/A
Rear Panel External I/O	Flexible IBASE Mini-ITX motherboard's I/O shields, 3x COM ports, extra 2x USB port, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors, 1x PCI expansion slot
Storage	1x 2.5" HDD drive bay
Power Supply	Output Power: DC 60W or 85W (ATX Power) Input Voltage: 115~230VAC (Nom.)
Mounting	Desktop or wall mount
Dimensions	300mm(W) x 200mm(D) x 72mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CM1201-60	Chassis for Mini-ITX (low power), w/ 60W PSU, 2.5" HDD holder, 1x PCI-E (optional IP271-R, IP119-R riser & LVDS/DVI ports)
CM1201-85	Chassis for Mini-ITX (low power), w/ 85W PSU, 2.5" HDD holder, 1x PCI-E (optional IP271-R, IP119-R riser & LVDS/DVI ports)

* Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.