
GOT3157W-881-PCT

15.6" WXGA TFT Fanless Multi-touch Panel Computer with LGA1150 Socket 4th Gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® Processors (0°C to +40°C)

Features

- 15.6" WXGA projected capacitive multi-touch screen
- Fanless design with LGA1150 socket 4th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processors (Haswell)
- 2.5" SATA HDD, CFast™ and mSATA
- WLAN module and antenna (optional)
- 2 Gigabit LANs, 2 USB 3.0, 2 USB 2.0 & 2 COM ports
- IP65 front bezel and rugged design
- Supports panel mount and optional VESA arm/desktop stand/ wall mount
- 2 PCI Express Mini Card slots





Introduction

The GOT3157W-881-PCT adopts a 15.6-inch WXGA LCD and supports LGA1150 socket 4th generation Intel® Core™, Pentium® and Celeron® processors. It can run Windows® 7, Windows® 7 Embedded, Windows® 8, Windows® 8 Embedded for a variety of applications. This 15.6" WXGA industrial touch panel PC has abilities below to make it surely a robust and reliable solution.

High Performance Haswell Desktop Processor


The G0T3157W-881-PCT supports LGA1150 socket 4th generation Intel® Core™ and Celeron® Haswell processors. Users can choose different processor upon request. It also supports up to 8 GB DDR3-1333/1600 MHz memory. Rich I/O includes dual PCI Express Mini Card slots, 2.5" HDD drive bay, USB 3.0 port, RS-232/422/485 and HDMI interface.


Reliable and Stable Design

The GOT3157W-881-PCT is a fanless cooling panel system designed for industrial machinery market. The Intel® Haswell panel PC can work under 1.0 G (10 ~ 500Hz, random for CFast™ card) in operation mode with a patent of anti-vibration design. The patent improves the system reliability and sustainability.

15.6-inch WXGA LCD with Projected Capacitive Multi-touch

The 15.6" WXGA Intel® Haswell-based touch panel PC supports 400 nits high brightness and can display contents in HD resolution. With projected capacitive multi-touch screen, users can operate more intuitively and directly. The hardness of touch glass surface is up to 7h and is better for anti-scratch purpose.





Power switch (ATX)
Power input connector
Audio (Line-out)
Audio (Mic-in)
COM 1/2 (RS-232/422/485)

7. Gigabit LAN x 2 8. USB 2.0 x 2 9. USB 3.0 x 2 10. CFast™ card slot Antenna x 3
LED backlight power On/Off

- 13. Brightness +
- 14. Brightness -

Specifications

IP65 front bezel	
Display Type	15.6" WXGA TFT LCD
Brightness (cd/m ²)	400 nits
Resolution	1366 x 768
CPU	LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processors (Haswell), up to 45 W TDP
Chipset	Intel® H81
System Memory	1 x 204-pin DDR3-1333/1600 SO-DIMM, up to 8GB
BIOS	AMI UEFI BIOS
Storage	1 x 2.5" SATA HDD 1 x CFast™ card 1 x mSATA
Watchdog Timer	255 levels, 0~255 sec.
Onboard Graphics	Integrated Intel® HD Graphics
	Display Type Brightness (cd/m²) Resolution CPU Chipset System Memory BIOS Storage Watchdog Timer

Specifications

-	
I/O Connector	2 x RS-232/422/485 (COM 1/2) 1 x Switch for power on/off (ATX) 2 x Audio (Line-out & Mic-in) 2 x USB 3.0 2 x USB 2.0 1 x HDMI
	2 x 10/100/1000 Mbps Ethernet (Intel® i219LM/i211AT)
Expansion Interface	2 x PCI Express Mini Card slot
Touchscreen	Projected capacitive multi-touch
Power Supply	19 VDC with adapter
Power Consumption	100 W
Dimensions	396.8 mm (15.6") (W) x 89.5 mm (3.5") (D) x 247.1 mm (9.73") (H)
Packing Dimensions	525 mm (20.67") (W) x 186 mm (7.32") (D) x 470 mm (18.51") (H)
Weight (net/gross)	5.5 kg (12.13 lb)/7.5 kg (16.53 lb)
Environment	Operating temperature: 0°C ~ +40°C (+32°F ~ +104°F) Relative humidity: 20% ~ 90% @ 40°C; non-condensing Operation vibration: 1.0 G, 10 ~ 500 Hz, random for CFast™ card
Certificate	CE

Ordering Information

GOT3157W-881-PCT-NP	15.6" WXGA TFT fanless touch panel computer with LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processors, projected capacitive multi-touch screen and AC-DC 19 VDC power adapter (power DIN 4P connector)
---------------------	---

Optional EOS Installation

WE8S WES 7	Optional OS Installation	า
WE8S	WES 7	
	WE8S	

Windows® 8.1

Windows® 7



▲ Ideal for factory automation & self-service kiosk in retail

Dimensions

