



Features

- Mini-ITX system supports IBASE MI802 Mini-ITX motherboard
- Intel® Atom™ D2550 processor
- Supports 5x RS232 & 1x RS232/422/485
- 6x USB 2.0 ports
- 1x Digital I/O 4-in 4-out
- Supports 2x Mini PCI-E / 1x PCI expansion slot
- Supports 1x 2.5" SATA HDD drive bay
- Wall mount kit included

Specifications

System Mainboard	MI802 / MI802N
CPU Type	Intel® Atom™ D2550 / N2600 processor
System Speed	1.86GHz / 1.66GHz
Memory	2x DDR3-1066 SO-DIMM, Max 4GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	8x COM (optional) 1x Power/HDD LED 2x USB 2.0 1x Power On/Off rock switch
Rear Panel External I/O	6x COM (serial ports) 1x VGA, 1x DVI-D 4x USB 2.0 1x PS/2 keyboard + mouse 2x RJ45 (Gigabit LAN) 1x Audio jack (Line out, Line in, Mic in) 2x slots for PCI card 1x 12V~24V DC-in (3-pin terminal block) 1x Digital I/O 4-in 4-out (10-pin terminal block)
Storage	1x 2.5" HDD/SSD bracket
Power Supply	84W power adaptor Input voltage :90V ~ 264V Input frequency :47Hz ~ 63Hz
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	300mm(W) x 235mm(D) x 83mm(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 1g / 5~500Hz / random operation
Certification	CE, FCC

Ordering Information

CMI222-802	Chassis with MI802 Mini-ITX, 320GB SATA HDD, 4GB DDR3 memory, w/o 84W power adaptor
CMI222-802N	Chassis with MI802N Mini-ITX, 320GB SATA HDD, 2GB DDR3 memory, w/o 84W power adaptor for fanless system

Dimensions and Drawing

