

# CVR-4300

FreeScale, MPC-8360

## FEATURE

- Powered by FreeScale MPC-8360
- 24 Gb Ethernet ports LAN connection
- 4 TDM/PCM channels for T1/E1 connection
- V.90 interface
- 2 FXO & 6 FXS connection
- Optional DSP & PoE module
- Mini-PCI socket for wireless application



## SPECIFICATION

CPU Board	Built with FreeScale MPC-8360
System Memory	- Onboard un-buffered, none-ECC DDR2 128MB - Up to 256MB expandable
Network Interface	- 12 or 24 10/100/1000 GbE switching LAN ports w/ PoE (optional) - 1 x 10/100 FE WAN port - 1 x V.90 Modem port
PSTN Interface	- 6 FXS ports - 2 FXO ports
Serial Port	One RJ45 connector for system console through RS232
LEDs	LED indicators for power and status
USB	Dual USB 2.0
Power	200W AC-DC
Dimension	443 (W) x 336 (D) x 44 (H) mm 17.45" (W) x 13.23" (D) x 1.73" (H)
Operating Environment	- Temperature: 5 to 40°C (41 to 104°F) - Humidity 20% to 90% RH
Storage Environment	- Temperature: 0 to 70°C (32 to 158°F) - Humidity 5% to 95% RH
Certification	CE/FCC/UL



## ORDERING GUIDE

Part No.	CPU	T1/E1	WAN	LAN	FXS	FXO	DSP	PoE
CVR-4300-6240	MPC-8360	4	1	24	6	2	Optional	Optional

\* Specifications are subject to change without notice.

\* Other trademarks, logo, brands and company names are the property of their respective owners.