

MEDS-1061

Embedded slim system support Intel® 4th Generation Core™ family with Display Port, Dual Gigabit Ethernet, and USB 3.0



SYSTEM

CPU/ Chipset	Intel® 4th Gen. Core™ processor with C226 Chipset
BIOS	AMI BIOS
System Memory	One 204-pin SO-DIMM slot up to 16GB DDR3L 1600MHz
Storage	- 1 x mSATA - 1 x HDD (Optional)
Watchdog Timer	Programmable via S/W from 1sec. to 255min.
H/W Status Monitor	- Temperature (CPU and System) - Voltage (CPU Vcore, VBAT, 5VSB, 12V, 5V, 3.3V)

REAR PANEL

Audio	Realtek ALC892 HDA codec
Display	1 x Display Port (2560x1600), VGA (Optional) (1920 x 1200)
USB	2 x USB 3.0 (Front), 2 x USB 2.0 (Rear)
Ethernet	2 x Gigabit Ethernet
Serial Port	One Selectable RS232/422/485 port (Optional)

Power Supply Unit

Power Input	DC 12V
Adaptor	AC 100-240V

MECHANICAL & ENVIRONMENTAL

Operation Temperature	5-40°C
Storage Temperature	5-40°C
Relative Humidity	5-95% non-condensing
Dimension (HxWxD)	6" x 1.75" x 8.3" (HxWxD)

FEATURES

- Intel® 4th Gen. Core™ processor
- up to 16GB DDR3L SO-DIMM
- Two Intel Gigabit Ethernet
- Support DC 12V input
- Versatile mounting solutions such as Wall, Panel and DIN mount (optional)

REAR I/O



ORDERING GUIDE

- **MEDS-1061** Compact System based on Intel 4th Gen. Core™ Processor



American Portwell

44200 Christy Street,
Fremont, CA 94538, USA
Tel: +1-510-403-3399
Fax: +1-510-403-3184
E-mail: info@portwell.com
<http://www.portwell.com>