# **Gladius** 10

# 10.1" Rugged Android™ Handheld Device with Qcta-core Processor

•



## Features


- Fully rugged for warehousing / transportation / medical / mPOS applications
- MIL-STD-810G & IP-65 certified, 1.5m (5ft.) drop resistance
- 10.1"TFT color LCD 1280 x 800 HD resolution
- Projected capacitive multi-touch panel with anti-reflection Corning<sup>®</sup> Gorilla<sup>®</sup> 3 Glass
- High mobility with multiple connectivities including WLAN, Bluetooth and WWAN
- Built in 1D/2D BCS (Barcode Scanner)
- Field replaceable battery with optimized battery life up to 18 hours
- Wireless charge supported
- G sensor, Gyroscope, light sensor, E-compass, GPS navigation and Barometer
- · System access control via RFID & NFC reader

Durability Featu	res	
MIL-STD-810G & IF	2-65 certified	
1.5m (5ft.) drop-res	istance	
Raised bezel for LC	D impact protection	
I/O ports with hinge	d rubber covers	
System		
CPU	MTK MT8392 Octa-core Cortex™A7 2.0GHz CPU Quad-core ARM Mali 3D GPU	
OS	Android™ v4.4	
Memory	2GB	
Storage	16GB	
Audio	Integrated microphone	
	Integrated speaker	
	1 x 3.5mm stereo headphone jack	
Peripherals and		
Camera	Front: 2.0 megapixel camera	
	Rear: 13.0 megapixel AF camera with flash	
Sensor	Accelerometer (G-sensor)	
	3-axis Digital Gyroscope Barometer	
Light Sensor	Ambient light sensor	
RFID & NFC	•	
WLAN	ISO/IEC 21481 Type A, Type B, Felica Integrated IEEE 802.11 b/g/n	
	Wi-Fi certified Miracast™	
Bluetooth	Integrated Bluetooth 4.0 + EDR class 1, with HID input, A2DP, DUN, HFP, SPP & PBAP supported	
WWAN	3G HSPA+(21/5.76 Mbps)	
Navigation	GPS, AGPS & E-compass	
Barcode Scanner	1D or 1D&2D barcode scanner with physical trigger button	
I/O Interface		
USB Port	1 x Micro USB 2.0 port	
SD Slot	1 x microSD card slot	
SIM Socket	2 x SIM card slots	
HDMI	1 x Mini HDMI port	
Expansion	microSDHC	
•		

LCD Display			
Size/Type	10.1" TFT LCD		
Resolution	1280 x 800		
Touch Screen			
Туре	5-point Projected Capacitive Touch screen Corning <sup>®</sup> Gorilla <sup>®</sup> Glass 3 coating w/ anti-reflection coating		
Power Supply			
Power System	External AC power adapter		
Battery Type	Lithium-ion rechargeable battery		
	Field replaceable (for maintenance)		
	Wirelessly rechargable (only works with ARBOR wireless cradle and docking)		
Battery Capacity	3.8V, 9300mAh, 35.34Whr		
Battery Life	Up to 18 hours battery life with the following operations:		
	<ol> <li>Continuous audio playback of 160-Kbps encoded MP3 files</li> </ol>		
	<ol> <li>Internet browsing by Wi-Fi while:</li> </ol>		
	<ul> <li>Browsing snapshot versions of 20 separate web pages</li> </ul>		
	b. Using hourly push-email		
	Continuous video playback for 8 hours		
Adapter Input	Input: AC100~240C, 50~60 Hz		
Adapter Output	DC power output: 5V/2A		
Mechanical & En	vironmental		
Operating Temp.	0°C ~ 45°C (32°F ~ 113°F)		
Storage Temp.	-10°C ~ 60°C (-14°F ~ 140°F)		
Operating Humidity	95% (non-condensing)		
Dimensions (W x H x D)	278.4 x 190.7 x 22.9 mm (10.96" x 7.51"x 0.90")		
Weight	1060g (with battery)		
Ordering Informa	ation		
G101B	10.1" Android™ Rugged IoT Handheld Device with Qcta-core Processor, Front & Rear Camera and 10 Barcode Scanner		
G102B	10.1" Android™ Rugged IoT Handheld Device with Qcta-core Processor, Front & Rear Camera and 1E & 2D Barcode Scanner		



### Dimensions



#### **Standard Accessories**

	<b>X</b> • <b>1</b>
Rechargeable Li-ion battery pack	
Earphone	
	Manual
charger	
ess charger	
	y pack