

# AREMO-6163

6-slot full-sized industrial node chassis  
(Shoe-box)



## FEATURES

- One external 5.25" and two internal HDD drive bays
- Two USB ports on the front panel
- Can be vertically or horizontally mounted, easy to fit into space limited environment
- One 12 cm ball-bearing cooling fan for better ventilation
- One replaceable air filter for easily cleaning
- Two adjustable positions for hold-down card retainers provide better protection from vibration
- Both 6-slot ISA and PICMG backplane applicable; easy to change different backplanes
- Field replaceable power supply bracket for both normal PS/2 and PS/2 redundant power supply, easy for changing defective power supply

## ORDERING GUIDE

- **AREMO-6163-06P4-330X**  
6-slot full-sized industrial node chassis with 6-slot (4xPCI) PICMG backplane and 330W ATX power supply
- **AREMO-6163-06P4-D3501P**  
6-slot full-sized industrial node chassis with 6-slot (4xPCI) PICMG backplane and 350W Active PFC ATX power supply

## GENERAL

Construction	Heavy-duty steel
Drive Bay	External: 5.25" x1 Internal: 3.5" HDD x2
Card Retainer	Two locations for one card retainer
Air Filter	One replaceable air filter at the front door
Cooling Fan	One 12 cm ball-bearing fan
Indicator	Power on/off x1, HDD x1
Switch	Power on/off x1, System reset x1
Speaker	One 8 $\Omega$ speaker
Connector	Two USB ports on the front panel
Standard Color	Silver
Dimension	260(W) x 420.8(D) x 172(H) mm; 10.24"(W) x 16.56"(D) x 6.77"(H)
Weight	Net: 8.5 kg (18.7 lb); Gross: 9.5 kg (20.9 lb)
Backplane	PBP-06I: 6-slot PISA bus PICMG backplane PBP-06P4: 6-slot (4xPCI) PICMG backplane PBP-06P3: 6-slot (3xPCI) PICMG backplane

## POWER SUPPLY

### ORION-D3501P optional

Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	6A@90V
Efficiency	> 68%
Holdup Time	17 ms. at full load @25°C
Over Voltage Protection	+5V@ 7V; +3.3V@ 4.3V; +12V@ 15.6V
Over Power/Load Protection	Output power over to 110%~140%
MTBF	75,145 hrs
EMI & Safety Approval	UL, TUV, CE, FCC, CB, CSA, SEMKO, FIMKO, NEMCO, DIMCO
Temperature/Humidity	Operating: 0 ~ 50°C, 20 ~ 85%RH Storage: -40 ~ 70°C, 10 ~ 90%RH
Dimension (WxDxH)	150x140x86 mm; 5.9"x5.5"x3.4"

## ENVIRONMENT


Operating Temperature Range	0 to +50°C
Storage Temperature Range	-40 to +70°C
Relative Humidity	5% to 95%, non-condensing
Vibration	5~7 Hz: 0.5" double amplitude displacement 7~2000 Hz: 1.5g acceleration

# AREMO-6163

6-slot full-sized industrial node chassis  
(Shoe-box)

FEATURE	BENEFITS
<ul style="list-style-type: none"> <li>5.25" drive space for CD-ROM or mobile rack</li> </ul>	<ul style="list-style-type: none"> <li>Easy to install software</li> </ul>
<ul style="list-style-type: none"> <li>Two USB ports at the front</li> </ul>	<ul style="list-style-type: none"> <li>Easy to operate the system</li> </ul>
<ul style="list-style-type: none"> <li>One replaceable air filter</li> </ul>	<ul style="list-style-type: none"> <li>For easy cleaning</li> <li>Two USB ports equipped</li> </ul>
<ul style="list-style-type: none"> <li>Can be vertically or horizontally mounted</li> </ul>	<ul style="list-style-type: none"> <li>Easy to fit into different space limited environment</li> </ul>
<ul style="list-style-type: none"> <li>Two adjustable positions for hold-down card retainer</li> </ul>	<ul style="list-style-type: none"> <li>For fixing all the cards more flexibly and tightly</li> </ul>
<ul style="list-style-type: none"> <li>Both 6-slot ISA and PICMG backplane applicable</li> </ul>	<ul style="list-style-type: none"> <li>Easy to change to different backplane and keep stock</li> </ul>
<ul style="list-style-type: none"> <li>Field replaceable power supply bracket for both normal PS/2 power supply and PS/2 type redundant power supply</li> </ul>	<ul style="list-style-type: none"> <li>For ease of maintenance</li> </ul>

## WHAT'S NEW



**Two Adjustable Card Retainer Position**  
For fixing all the cards more flexibly and tightly



**Plastic Fan Filter**  
For easy cleaning and exchange



**New HDD Drive Design**  
Easy to install HDD drives

## ENGINEERING DRAWING

