

Industrial Single Board Computer

3.5 inch Miniboard LE-37D

Support Intel® Processor J1900/N2930/E3845 CPU with Onboard VGA, DVI, 2 x LVDS, Display port, HD Audio, Serial ATAII, USB3.0 & 2.0, Gigabit LAN, PCIE Mini card, mSATA



Form Factor	3.5 inch motherboard
CPU	Intel® Processor J1900/N2930/E3845, package type FCBGA1170
Memory	1 x DDR3L (support 1.35V) 1066/1333 DIMM up to 8GB
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset with internal timer for 1min/s ~ 255min/s
Power Management	Supports ACPI 5.0 compliant
Serial ATA Interface	1 x serial ATA interface with 300MB/s(3Gb/s) transfer rate
VGA Interface	Intel® Clear Video integrated HD Graphics Technology
DVI Interface	Onboard DVI connector. <i>(DVI and LVDS1 can't be enabled simultaneously)</i>
LVDS Interface	2 x Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply
Display port Interface	Onboard Display port connector. <i>(Display port and LVDS2 can't be enabled simultaneously)</i>
Audio Interface	Realtek ALC262 High Definition Audio Codec
LAN Interface	2 x Intel® I210 Gigabit LAN
GPIO interface	Onboard programmable 8-bit Digital I/O interface.
Extended Interface	2 x PCIE Mini card, 1 x SIM socket, 1x CFAST
Internal I/O Port	3 x RS232, 1 x RS232/422/485, 1 x GPIO, 1 x Audio connector, 1 x SMBUS connector, 1 x CRT, 2 x LVDS, 1 x LPC, 4 x USB 2.0(XHCI) and 1 x SATAII
External I/O Port	1 x RS232, 1 x DVI port, 1 x Display port, 2 x RJ45 LAN ports, 1 x USB 3.0(XHCI)/2.0(EHCI) port, 1 x USB 2.0 ports(EHCI).
Power Requirement	6~27V full range DC Input
Dimension	146mm x 101mm
Temperature	Operating within 0~60 centigrade Storage within -20~85 centigrade

Ordering Code

CRT, 2 x Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA

LE-37DJIP Intel Celeron Processor J1900 (2M Cache, 2.42GHz) DVI, Display Port

LE-37DJX2 Intel Celeron Processor J1900 (2M Cache, 2.42GHz) 2 x LVDS

LE-37DNIP Intel Atom Processor N2930 (2M Cache, 2.16GHz) DVI, Display Port

Taiwan Commate Computer Inc.

8F, 19F NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw



Stage For Your Success

Industrial Single Board Computer

LE-37DNX2	Intel Celeron Processor N2930 (2M Cache, 2.16GHz) 2 x LVDS
LE-37DEIP	Intel Atom Processor E3845 (2M Cache, 1.91GHz) DVI, Display Port
LE-37DEX2	Intel Atom Processor E3845 (2M Cache, 1.91GHz) 2 x LVDS

Taiwan Commate Computer Inc.

8F, 19F NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw



Stage For Your Success