



Specifications

System Mainboard	MI981AF
CPU type	4th generation Intel® Core™ i7/i5/i3 Desktop processors
System Speed	3.1GHz
Memory	2x DDR3-1600 4GB SO-DIMM [Non-ECC]
Construction	Steel
Chassis Color	Black
Front Panel External I/O	N/A
Rear Panel External I/O	2x DB9 for COM#1 COM#2 (COM1 RS232/422/485, select from BIOS) 6x USB 3.0 ports 2x RJ-45 GbE Connector 1x DVI-D, 1x VGA, 1x DisplayPort 1x Audio port for [Line-in / Line-out / Mic-in] 1x expansion slot 2x USB 2.0 ports 1x power on/off button, 1x reset button 1x power LED, 1x HDD LED 1x AC power-inlet 2x system fan 3x DB9 hole [Reserved] 1x DB9 for GPIO function
Storage	1x 3.5" or 2.5" HDD drive bay
Power Supply	250W power supply [FSP250-50GUB] Input voltage :100V ~ 240V Input frequency :47Hz ~ 63Hz
Mounting	Desktop or wall mount
Dimensions	345mm(W) x 225mm(D) x 100mm(H)
Operating Temperature	0°C~45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation
Certification	CE / LVD / FCC Class B

Features

- Mini-ITX system supports IBASE MI981 Mini-ITX motherboard
- Available in black color
- Supports 1x PCI-E(x16) slot
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- 250W power supply
- Wall mount kit included

Ordering Information

CM1203-981M	Chassis with MI981, w/ 250W PSU, 3.5" HDD holder, 1x PCI-E(x16), w/o CPU, HDD, Memory
-------------	---

Dimensions and Drawing

